

PRODUCT SPECIFICATIONS:

EACH TILE IS 12" X 12" X 1/8" SOLIDRUBBER

TILES CONTAIN 144 STUDS, ONE EVERY SQUAREINCH

STUDS ARE INSERTEDTHROUGH THE BACK OF THE TILE SO THAT THE FACE IS A SMOOTH SURFACE COMBINATION OF METAL STUDS ANDTILE

Hammered (SE)

Gauge: 1/8" (3.175 mm)

Design: Random Dimples across Surface

Design Depth: 0.010" - 0.015"

Size: 12" x 12" (30.48 cm x 30.48 cm),

Smooth (SM)

Gauge: 1/8" (3.175 mm)

Design: Smooth Surface

Size: 12" x 12" (30.48 cm x 30.48 cm),

TECHNICAL DATA, TESTING

PRODUCT CLASSIFICATION

ASTM F 1344, Rubber Floor Tile - Class I, Type A Solid Color

FIRE TESTING INFORMATION

ASTM E 648 (NFPA 253), Critical Radiant Flux - Class 1, > .45 W/cm²

ASTM E 662 (NFPA 258), Smoke Generation - Passes, < 450

GENERAL PERFORMANCE INFORMATION

ASTM D2047, Coefficient of Friction (Slip Resistance) - > .6

ASTM D2240, Hardness - > 85

ASTM D3389, Abrasion – Passes <1gm loss

ASTM F925, Resistance to Chemicals – Passes

ASTM F970, Static Load Limit - 250 psi, Passes Max Indentation of 0.003" @ 1,500 psi

PRODUCT BENEFITS & LIMITATIONS

- Can be installed over **radiant heat**, operational temperature must not exceed 85° to prevent damage to flooring
- Not to be used in **Commercial Kitchens** or other areas subjected to animal, vegetable or petroleum based oils and solvents.
- Not to be used in areas subjected to **sharp spikes, cleats, sharp wheels, stiletto heels** or other objects that could damage the flooring.
- Not to be used in direct contact with heat sources or in **outdoor** applications.

INSTALLATION:

- ◆ FLOOR MUST BE CLEAN AND DRY. REMOVE ANY OLD FLOOR COVERING AND BE SURE THE SUB FLOOR IS FREE OF ALL DIRT AND RESIDUE
- ◆ INSTALL QUALITY WHITE SHIELD FELT OR SATURATED PAPER WITH MULTI PURPOSE ADHESIVE
- ◆ ALLOW TO DRY THOROUGHLY
- ◆ USE A TWO PART EPOXY WITH A 1/8" X 1/8" SQUARE NOTCH TROWEL. SPREAD ADHESIVE AND INSTALL TILES WITH SMOOTH SIDE UP. ROLL WITH HEAVY FLOOR TILEROLLER
- ◆ FOR EASE OF CUTTING AT THE WALL, REMOVE STUDS FROM THE BACK BY PULLING OUT LIKE A THUMB TACK
- ◆ PUNCH OUT MATERIAL FROM HOLES AVAILABLE UPON REQUEST

MAINTENANCE:

SWEEP AND WASH FLOOR WITH A NEUTRAL PH CLEANER OR MILD DETERGENT AND WATER SOLUTION. FLOOR MUST BE DRIED WITH A SOFT CLOTH. **NEVER LEAVE FLOOR WET**

FOR PRODUCT SAMPLES PLEASE CONTACT CLASSIC TILE CUSTOMER

SERVICE 908- 289- 8400